

	DB, DBL 200	DK 200	DBK 200	DB 250	KK 200			K 350		KK 350	K 500		KS 500	KKS 500	K 800		
Zühnezahlen:																	
Hauptwelle   Vorgelegewelle					11	33		11	33	11	33	11	33	11	33	11	33
Kettenglieder	1. Gang				40			40		40		40		40		40	
"	2. Gang				13	25		13	25	15	27	13	25	15	27	15	27
"	3. Gang				36			36		38		36		38		38	
"	4. Gang				20	23		20	23	22	25	20	23	22	25	22	25
"					38			38		40		38		40		40	
"					22	21		22	21	25	22	22	21	25	22	25	22
"					38			38		40		38		40		40	
Vergaser																	
Fabrikat	Bing	Bing	Bing	Bing	Amal	Bing	Graetzin	Amal	Bing	Bing	Pallas	Amal	Amal	Amal	Amal	Amal	Amal
Typ	A/2/20/0	A/2/20/0	A/2/20/0	AJ 2/22	5/012	A/2/20	Ke 22	5/411	A/2/22F	A 2/22 F		4/407 S	5/418	75/422L.&R.	75/422L.&R.	5/406 SP	5/406 P
Kraftstoffdüse	75	75	75	90	75	80	85	90	85	85	110	65	85	100	100	150	150
Schieberausschnitt					5/3			5/3				4/3	5/2	5/4	5/4	5/2	5/2
Nadelstellung von oben Raste	1	1	1	2	2	2	2	1	1	1		2	3	2	2	2	2
Luftschraube-Umdrehungen offen	1,5-2	2	1,5-2	1	1,5	2-2,5	1,5	1,5-2	2,5	2,5		2	1,5	1	1	2,5-3	1 1/2
Leerlaufdüse							30				12						
Durchlaß in mm	20	20	20	22	22	20	22	22	22	22		20	22	22	22	22	22
Mischkammereinsatz Nr.	4	4	4	4					3	3							
Luftdüse											150						
Gargoyle Mobilöl																	
Art und -Menge in ccm																	
Motor	Sommer											DM 2000	DM 2000	DM 2000		DM 2500	
	Winter											Arctic 2000	Arctic 2000	Arctic 2000		Arctic 2500	
Getriebe	Sommer						DM 1000		DM 1000	DM 1000		DM 1000	DM 1000	DM 1000		DM 1000	
	Winter	Arctic 550	Arctic 550	Arctic 550	Arctic 550		Arctic 1000		Arctic 1000	Arctic 1000		Arctic 1000	Arctic 1000	Arctic 1000		Arctic 1000	
Kardan							Ep 180		Ep 180	Ep 180		Ep 180	Ep 180	Ep 180		Ep 180	
Zulässige Höchstbelastung in kg	160	160	160	160		160		180	180	180		200	200	180		200	
Tiefbettfelgen	19"×2,5"	19"×2,5"	19"×2,5"	19"×2,5"		19"×2,5"		19"×3"	19"×3"	19"×3"		19"×3"	19"×3"	19"×2,5" V		19"×3"	
														19"×3" H			
Bei K 800 W:																	
Bodenfreiheit in mm	130	130	150	130		130		130	130	130		110	130	125		110	130
Größte Breite in mm	750	750	750	750		750		815	815	815		815	815	815		815	915
Größte Länge in mm	2000	2080	2080	2000		2080		2150	2080	2080		2150	2150	2080		2165	
Sattelhöhe in mm	680	700	700	680		700		720	700	700		720	720	700		720	
Radstand in mm	1300	1335	1335	1300		1335		1390	1335	1335		1390	1390	1335		1405	

