


ZÜNDAPP

Elastic 250



With the more powerful engine of 250 cc.

There is nothing comparable with the roadholding of this model — submitting you new feelings of speed caused by noiseless and extremely smooth running of the engine as well as by the surprising effect of the brakes, moreover the magnificent beam of the headlight and the extraordinarily comfortable saddle. You just mean to ride for pleasure and yet you have reached an average of speed which was up to now believed to be impossible in this category.

Top security and riding-culture are the results of the elaborate working-manner of this machine.



PROVIDENCE CYCLE CO.

314 BROAD STREET

PROVIDENCE, RHODE ISLAND

CAN 1-2537



TECHNICAL DETAILS


Engine: ZUNDAPP two-stroke block-type engine, bore 67 mm (2.64"), stroke 70 mm (2.76"), capacity 246 cc. (15 cu. in.), compression ratio 1:6.7; 14 HP at 5200 r.p.m., two-slide carburetor with oblique jet with especially effective damping of suction noise and with separate air control. Mixture type lubrication, maximum speed 100 km/h = 61 mph when driver sitting, 120 km/h = 75 mph when driver lying.

Gearing and Transmission: Zündapp four-speed gear box (selector friction shaft with cams) with foot gear change, gear box with engine in one block. Transmission ratios: 1:3.14—1.964—1.425—1.00. Reduction ratio from engine to gear box 1:1.28. Reduction ratio from gear box to rear wheel 1:3.44. Multiple disc clutch in oil bath, transmission chain to rear wheel.

Carriage, measures etc.: Central tube frame, telescopic fork of long stroke, broad-positioned rear wheel, swinging arm permanently oil-lubricated with adjustable oil-damped spring legs, total spring action 95 mm (3.9"), cylindrical hub brakes 160 mm (6.3") Ø, lining 30 mm (1.2"). Broad tubular center stand, handlebar and footrests adjustable, closed chain case, rear wheel with knockout spindle, removable end of rear mudguard. Large front rubber saddle with additional coil springs, to be turned up, easier to be disassembled, long footbrake lever with adjustable stop, handy controls. Deep center rims 1.85-8 x 19 with steel wire balloon tires. Front wheel 7.00-19, rear wheel 3.25-19. Wheel base approx. 1350 mm (53.2"), total height approx. 740 mm (29.1"), saddle height approx. 740 mm (29.1"), ground clearance approx. 160 mm (6.3"), admissible maximum load 156 kgs (344 lbs), total weight — in running order with filled tank 147 kgs (324.3 lbs), capacity of tank 14.7 liters (3.9 US gall., 3.2 Imp. gall.).

Equipment: 60/70 Watt battery-lighting-ignition system, with 25/35 Watt Bilux lamp, brake and clutch Bowden cables adjustable at the levers, illuminated speedometer dial in headlamp, steering damper, springlegs adjustable according to load, surprisingly quiet suction and exhaust, separate air control, extremely ample chrome plating and many polished parts, best high polish enamel finish, ample set of tools and air pump dustproof enclosed in the saddle. Antithrottling device. Varnish: black, red or light-green.

Code word: ELFUENF



The ZUNDAPP-ELASTIC, standing the roughest tests also when driven with sidecar, surprises you by the tremendous power of its engine, climbing capacity, excellent roadgripping and high security on winding roads.

We reserve the right to alter construction.

Printed in Germany

ZUNDAPP WERKE GMBH / NÜRNBERG-MÜNCHEN
WERK NÜRNBERG